

January 11, 2010

INVITATION TO BID # 10-06

Sealed bids for Police Department uniform items for the City of Birmingham for a period of one (1) year with month to month extensions thereafter upon mutual consent of both parties, will be received by the Purchasing Agent, P-100 First Floor City Hall, Birmingham, Alabama until 2:00 p.m., February 9, 2010, at which time they will be publicly opened and read.

Bidders wishing to bid can download the complete solicitation including the specifications and bid forms via the internet at www.birminghamal.gov (go to link titled **Bidding Opportunities**), or by visiting the Purchasing Office at the address shown above, or by calling (205) 254-2265, fax (205) 254-2484 and requesting a copy be mailed to you. Any addenda will be available on the internet, and mailed to only those vendors who were provided a copy in person or by mail.

It is required for any contract exceeding \$10,000.00 that the bidder submit with his bid either a certified check, a cashier's check, or a bid bond payable to the City of Birmingham. In order for any award to be considered that exceeds \$10,000.00, your bid must have been accompanied by an acceptable bid bond or check in the amount of \$500.00.

The City follows a policy of nondiscrimination. No contractor with the City should discriminate on the basis of race, sex, religion or national origin. The City considers affirmative action to eliminate the vestiges of discrimination to be an integral part of this policy of nondiscrimination.

No bid may be withdrawn for a period of sixty (60) days after the date of the bid opening.

The City reserves the right to reject any or all bids submitted, and to waive any informalities.

Bids must be submitted in a sealed envelope marked, "**POLICE UNIFORM ITEMS, 2:00 P.M., 02/09/10**". Bids may be hand delivered to P-100 First Floor City Hall, Birmingham, Alabama or mailed to City of Birmingham, P.O. Box 11295, Birmingham, Alabama. 35202-1295. (DO NOT MAIL BIDS TO ROOM P-100 FIRST FLOOR CITY HALL). However, bids sent by express carrier (Federal Express, Airborne, UPS, etc) must be shipped to 710 North 20th Street, Birmingham, AL 35203 and specify delivery to Room P-100 FIRST FLOOR City Hall.

It is the bidder's responsibility to make sure that his bid is in the possession of the Purchasing Agent on or before 2:00 p.m., February 9, 2010. Bids received after this time will not be considered.

William E. Caffee, Assistant. Purchasing Agent

cl

BN 01/210

SPECIFICATIONS FOR UNIFORM ITEMS FOR THE BIRMINGHAM POLICE DEPARTMENT

GENERAL

The City of Birmingham is seeking bids for various uniform items for the Birmingham Police Department as specified later in this document. The uniform shirts and trousers/slacks are considered custom, made to order, items. The City intends to award as follows: Group (1) all uniform shirts will be awarded as a lot to the lowest priced responsible, responsive bidder; Group (2) all uniform trousers/slacks will be awarded as a lot to the lowest priced responsible, responsive bidder; Group (3) all rainwear will be awarded as a lot to the lowest priced responsible, responsive bidder; Group (4) Jail dress uniform items will be awarded as a lot to the lowest priced responsible, responsive bidder for the base bid, alternate or any combination thereof.

The proposed contract shall extend for a minimum time frame of one (1) year, with a month to month extension thereafter, at the prices originally bid, upon mutual agreement of both parties. This extension phase is not to exceed twenty-four (24) months. Prior to the end of the initial contract year or during any extension phase of this contract, the successful bidder(s) shall give the City an advanced thirty (30) days written notice of intent not to extend the contract. The life of this contract shall exist with the provision that no price increase in the original bid prices shall be allowed.

The quantities shown on the bid form for Groups 1 and 2 are the estimated initial purchase. The quantities shown on the bid form for Groups 3 and 4 are estimated annual quantities only. Merchandise shall be ordered as requirements dictate. The City reserves the right to purchase more or less than these quantities as conditions require, and no bidder shall attempt to hold the quantities shown as a firm quantity under this contract.

Bidders are to bid one unit price for each of the items listed in Groups 1, 2 and 3. The City will not consider any bid that offers different unit prices for the same line item based on variation in size. Bidders are to average cost items to come up with a single unit price for each line item – regardless of size. Items in Groups 4 are to be priced as indicated on the bid form.

The City's standard payment terms are net 30 days from acceptance. Exception may be allowed for discounted early payment, such as 2% 10 net 30 days. The City will not consider any bids requiring C.O.D. payment.

Successful bidder(s) shall not assign this contract to any other party without prior written approval of the City of Birmingham. Contract shall not be assigned to an unsuccessful bidder who was rejected because he was not a responsive or responsible bidder.

Any questions concerning these specifications should be addressed to Charles Lindsey, Purchasing Division, Phone: (205) 254-2265 or Fax: (205) 254-2484, between the hours of 8:00 a.m. and 4:00 p.m. CDT, Monday thru Friday.

Contract award to purchase the materials covered in this bid document shall be construed under and governed by the laws of the State of Alabama and each party hereto irrevocably agrees to be subject to the jurisdictions of the courts of the State of Alabama.

The City of Birmingham does not anticipate utilization of a long, formal, written contract document to bind the City and the successful bidder(s) to an agreement. The City will issue purchase orders to the successful bidder(s) as material is required. The successful bidder(s) acknowledge by acceptance of the City purchase orders for awarded items that the bidder is bound to the terms, conditions and requirements as stated in this document.

All bids submitted for Groups 1, 2 and 3 are to be f.o.b. City of Birmingham, Police Distribution Center, 1710 1st Avenue North, Birmingham, Alabama 35203, Monday through Friday, 8:00 a.m. to 4:00 p.m.

The contract shall become effective from the date noted in the Notification of Award letter, which will be mailed to the successful vendor.

Failure to adhere to any or all terms, conditions and specifications as set forth in the contract may result in the immediate termination of the contract. Should termination occur, the holder of the contract may be declared a "non-responsible vendor". This declaration may result in the rejection of any future bids submitted by the vendor for a period of time to be determined by the City.

The City reserves the right to cancel the contract for any item(s) and seek new bids at anytime the City determines that the work wear being supplied is failing to perform satisfactorily. Examples of such unsatisfactory performance shall include, but not limited to; excessive shrinkage, excessive fading, unraveling of seams or hems, poor fits, poor workmanship, etc.

Each bidder is to extend unit prices and provide an extended total for each line item being bid. If the extended totals of all items being bid exceed \$10,000.00, a bid bond, a cashier's check, or certified check in the amount of \$500.00 is required to accompany your bid. Each bidder is to extend unit price and provide an extended total for each line item being bid. If the extended total of all items being bid exceeds \$10,000.00, a cashier's check, certified check, or a bid bond in the amount of \$500.00 is to accompany your bid.

In order for any bid award to be made that exceeds \$10,000.00, bid must have been accompanied by an acceptable bid bond or check (REFERENCED ON THE COVER LETTER "INVITATION TO BID").

Any bid that imposes a service fee or any other type of fee on any order not exceeding a minimum order quantity or minimum purchase order dollar amount, will be determined a non-responsive bid and will not be considered for award.

Bidder shall check (✓) each and every paragraph in the appropriate column provided on the right hand edge of the page as to compliance or non-compliance with specifications. These sheets are to be returned with the signed and completed bid form. Exceptions will be allowed to items that are not listed as "No Exception" if they are equal to or superior to that specified and provided that they are listed and fully explained on the Exceptions page. The City shall be the sole judge of equivalency and the decision of the City of Birmingham shall be final. Bids taking total exception to the specifications will not be accepted.

Bids for Group 4 will be accepted only from established firms engaged in the business of stocking, selling or renting uniforms within the combined areas of Jefferson County and the corporate city limits of Birmingham, AL. A minimum stock of the uniform items indicated on the bid form from which the City can pick-up as needed will be required. Items not in stock that must be ordered shall be delivered within thirty (30) days of receipt of purchase order and proper size requirements, whichever is the latter. Repetitive late deliveries will be grounds for termination of the contract. However, late deliveries due to documented interference by City personnel will not be held against the vendor.

Successful bidder for Group 4 will be required to measure each City employee to ensure proper fit. Bid price will include any common alterations required for proper fit: Trousers and shorts – waist, seat, length; Shirts – no alterations. Charges for any other alterations will have to be approved by the appropriate department and billed separately. All items are to be delivered to the delivery location provided on each purchase order. Items are to be shipped as a complete quantity at one time – no partial shipments. Items are to be wrapped, boxed, bagged, etc. and properly identified with employee name, if provided, and purchase order number.

All bids submitted for Group 4 are to be f.o.b. City of Birmingham, City Jail, 425 6th Avenue South, Birmingham, AL 35205, Monday through Friday, 8:00 a.m. to 4:00 p.m.

Successful bidder(s) acknowledges and agrees that the City has the right to deduct from total amount of consideration to be paid, if any, to the successful bidder under this agreement all unpaid, delinquent or overdue license fees, taxes, fines, penalties and other amounts due the City from the successful bidder.

City of Birmingham must have a copy of the successful bidder's current City of Birmingham business license prior to formal award of contract. Each bidder may submit a copy of his/her license along with his/her bid. However, successful bidder must provide a copy of his/her current business license no later than 7 working days of receipt of notice of intent to award. Failure to submit the requested information will result in the notice of intent to award being revoked.

<p align="center">SPECIFICATIONS FOR CITY OF BIRMINGHAM POLICE DEPARTMENT Men's summer shirts (short sleeve) Group 1</p>	Bidder Complies	
	Yes	No
<p><u>STYLE:</u> It is the intention of this department to secure a tailored shirt equal in quality of workmanship, style and color to the shirt now on display as a sample. Sample shirt to be provided to lowest apparent bidder upon request. The style shall be cut on a semi form-fitting line, short sleeve with full length tails. The shirt to have two outside breast pockets and scalloped flaps having one button each. Also to have full badge sling on left side and shoulder straps. The back to have a double yoke with High Lustre Venetian band and yoke trim.</p> <p><u>FABRIC:</u> Raeford Mills #3906-30 (Midnight Blue), 1 ply 75/25 Dacron Polyester/Worsted Wool Permanent Press in a tropical weave weighing 10 to 10-1/2 oz. Per linear yard. Shoulder Straps shall be #3906-604, 75/25 Dacron Polyester/Worsted Wool Permanent Press in a tropical weave. (Lowest apparent bidder to supply verification of material style and color from Raeford Mills in letter form to the Police Department prior to shipment.)</p> <p><u>COLOR:</u> Midnight blue (Color MUST match that of sample shirt).</p> <p><u>COLLAR:</u> Convertible collar shall be one piece and to measure 3-1/4" long at points. The back of the stand is to measure 1-1/2". Collar to be top stitched 1/4" off the edge. The collar is to be constructed of two plies of basic material and one ply of top fuse lining. The collar shall be made with permanent collar stays. Stays to be attached to bottom collar. Innerstand and inner yoke to be made of matching 65% Dacron Polyester/35% Combed Cotton, poplin fabric.</p> <p><u>SHOULDER STRAPS:</u> The shoulder straps shall be pointed at the end toward the neck of the shirt. The other end shall be sewn in sleeve head seam. The pointed ends shall be fastened with one matching button. The strap shall measure 2" at sleeve and tapered to 1-3/8". Straps are to be set about 1/2" from the collar. Shoulder straps shall be box-stitched to shoulders with row of cross stitching 2" from sleeve head seam and diagonally across from each end seam to the sleeve head seam.</p> <p><u>BADGE REINFORCEMENT:</u> Shall have a 2 ply sling-type badge reinforcement inside left front of shirt 1-1/8" wide to be centered and secured in left shoulder seam and left flap setting seam. Two buttonhole eyelets are to be spaced approximately 1-1/4" apart with the bottom eyelet approximately 1-1/4" from the top of the left pocket flap.</p> <p><u>FRONT:</u> Each front shall have a facing 3" in width extending from neckline to bottom of shirt provided by a turn-under of material. The left front shall also have a lined box pleat 1-1/2" wide finished, running full length of the shirt and shall be topstitched 1/4" from both edges. The left front shall have 7 buttonholes 3/4" from edge. Second buttonhole to be positioned 3" from top horizontal buttonhole, balance of buttonholes to be vertically spaced 3-1/2" apart on center. Buttons to be strongly attached through two thicknesses of material sewn on the right front, and shall correspond to each buttonhole.</p> <p><u>PERMANENT CREASES:</u> Shall have five (5) permanent military creases using the Lintrak method. Two creases on the front to be centered vertically through each pocket and flap and three creases on the back proportionately spaced.</p>		

SPECIFICATIONS FOR CITY OF BIRMINGHAM POLICE DEPARTMENT Men's summer shirts (short sleeve cont'd) Group 1	Bidder Complies									
	Yes	No								
<p><u>SHORT SLEEVES:</u> Sleeves are to be straight and whole, to have 1" hem and to finish from shoulder seam as follows:</p> <table border="0"> <tr> <td><u>SIZE</u></td> <td><u>FINISHED LENGTH</u></td> </tr> <tr> <td>14 AND 14-1/2</td> <td>9-1/2"</td> </tr> <tr> <td>15, 15-1/2 AND 16</td> <td>10"</td> </tr> <tr> <td>16-1/2 AND ABOVE</td> <td>10-1/2"</td> </tr> </table> <p><u>POCKETS:</u> To have two breast pockets with 1-1/4" stitched down pleat. Pocket to finish 5-5/8" wide and 6" deep. The left breast pocket to have a pencil stitch approximately 1-1/4" wide.</p> <p><u>FLAPS:</u> To have two scalloped flaps, to finish 5-3/4" in length, 2-3/4" in width at center point and 2-1/2" at sides. Flaps to be secured to front of shirt approximately 1/4" above top of pocket. The left flap to have a pencil opening about 1-1/4" in width. A button is to be centered and secured 3/4" above the center scalloped point on each flap.</p> <p><u>VELCRO CLOSURE:</u> Each pocket flap shall have a rectangular strip of Velcro tape measuring approximately 1" X 3/8" wide on each of the outer points. Velcro tape of the same size shall be properly positioned on the pockets to engage the tape on the flaps when closed.</p> <p><u>SEWING:</u> All stitches must be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give the best durable press performance. Collars, shoulder straps and flaps shall be single stitched 1/4" from the edge. The back yoke and joining seams shall be single-stitched on the edge. Sleeve insertion and side closing to be safety stitched. All sewing shall be of 100% Dacron matching thread.</p> <p><u>BUTTONS:</u> All buttons shall be made from thermo-setting polyester material and must match fabric.</p> <p><u>INTERLINING:</u> Collar and flaps to be interlined with Stabilized Mello-Press interlining.</p> <p><u>EMBLEM:</u> Shirts to have Birmingham Police Emblem attached to left sleeve and centered approximately one (1) inch below shoulder seam. Emblems to be furnished by the City of Birmingham to the successful bidder.</p> <p><u>SIZE MARKING:</u> Neck size shall be marked with indelible ink on a size loop attached to basic label in yoke and on outside of left front tail.</p> <p><u>PRESSING AND PACKING:</u> Shirts shall be carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts are to be shipped in strong boxes so as not to be damaged in shipment. Shirts to be packed twelve to a box with the same sizes marked on the outside of the box at one end.</p> <p>NOTE: Successful bidder shall furnish a pre-production sample in a men's size 17- 17 1/2 for inspection before full production begins.</p>	<u>SIZE</u>	<u>FINISHED LENGTH</u>	14 AND 14-1/2	9-1/2"	15, 15-1/2 AND 16	10"	16-1/2 AND ABOVE	10-1/2"		
<u>SIZE</u>	<u>FINISHED LENGTH</u>									
14 AND 14-1/2	9-1/2"									
15, 15-1/2 AND 16	10"									
16-1/2 AND ABOVE	10-1/2"									

<p align="center">SPECIFICATIONS FOR CITY OF BIRMINGHAM POLICE DEPARTMENT Women's summer shirts (short sleeve) Group 1</p>	Bidder Complies	
	Yes	No
<p>STYLE: It is the intention of this department to secure a tailored shirt equal in quality of workmanship, style and color to the shirt now on display as a sample. Sample shirt to be provided to lowest apparent bidder upon request.</p> <p>The style shall be cut on a semi form-fitting line, short sleeve with full length tails. The shirt to have two outside breast pockets and scalloped flaps having one button each. Also to have full badge sling on left side and shoulder straps. The back to have a double yoke with High Lustre Venetian band yoke trim.</p> <p>FABRIC: Raeford Mills #3906-30 (Midnight Blue), 1 ply 75/25 Dacron Polyester/Worsted Wool Permanent Press in a tropical weave weighing 10 to 10-1/2 oz. Per linear yard. Shoulder Straps shall be #3906-604, 75/25 Dacron Polyester/Worsted Wool Permanent Press in a tropical weave. (Lowest apparent bidder to supply verification of material style and color from Raeford Mills in letter form to the Police Department prior to shipment.)</p> <p>COLOR: Midnight blue (Color MUST match that of sample shirt).</p> <p>COLLAR: Convertible collar shall be one piece and to measure 3-1/4" long at points. The back of the stand is to measure 1-1/2".</p> <p>Collar to be top stitched 1/4" off the edge. The collar is to be constructed of two plies of basic material and one ply of top fuse lining. The collar shall be made with permanent collar stays. Stays to be attached to bottom collar.</p> <p>Innerstand and inner yoke to be made of matching 65% Dacron Polyester/35% Combed Cotton, poplin fabric.</p> <p>SHOULDER STRAPS: The shoulder straps shall be pointed at the end toward the neck of the shirt. The other end shall be sewn in sleeve head seam. The pointed ends shall be fastened with one matching button. The strap shall measure 2" at sleeve and tapered to 1-3/8". Straps are to be set about 1/2" from the collar. Shoulder straps shall be box-stitched to shoulders with row of cross stitching 2" from sleeve head seam and diagonally across from each end seam to the sleeve head seam.</p> <p>BADGE REINFORCEMENT: Shall have a 2 ply sling-type badge reinforcement inside left front of shirt 1-1/8" wide to be centered and secured in left shoulder seam and left flap setting seam. Two buttonhole eyelets are to be spaced approximately 1-1/4" apart with the bottom eyelet approximately 1-1/4" from the top of the left pocket flap.</p> <p>FRONT: Each front shall have a facing 3" in width extending from neckline to bottom of shirt provided by a turn-under of material. The right front shall also have a lined box pleat 1-1/2" wide finished, running full length of the shirt and shall be topstitched 1/4" from both edges.</p> <p>The right front shall have 7 buttonholes 3/4" from edge. Second buttonhole to be positioned 3" from top horizontal buttonhole, balance of buttonholes to be vertically spaced 3-1/2" apart on center. Buttons to be strongly attached through two thicknesses of material sewn on the left front, and shall correspond to each buttonhole.</p>		

<p style="text-align: center;">BIRMINGHAM POLICE DEPARTMENT Women's summer shirt (short sleeve cont'd) Group 1</p>	Bidder Complies	
	Yes	No
<p><u>FIT:</u> Shirts are to have two darts, one on each side, in front to allow for waist suppression and two darts in back for waist suppression. Shirts are to be supplied in breast sizes.</p> <p><u>PERMANENT CREASES:</u> Shall have five (5) permanent military creases using the Lintrak method. Two creases on the front to be centered vertically through each pocket and flap and three creases on the back proportionately spaced.</p> <p><u>SHORT SLEEVES:</u> Sleeves are to be straight and whole, to have 1" hem and to finish 9" from shoulder seam.</p> <p><u>POCKETS:</u> To have two breast pockets with 1-1/4" stitched down pleat. Pocket to finish 5" wide and 5-1/2" deep. The left breast pocket to have a pencil stitch approximately 1-1/4" wide.</p> <p><u>FLAPS:</u> To have two scalloped flaps, to finish 5-1/4" in length, 2-3/8" in width at center point and 2-1/8" at sides. Flaps to be secured to front of shirt approximately 1/4" above top of pocket. The left flap to have a pencil opening about 1-1/4" in width. A button is to be centered and secured 3/4" above the center scalloped point on each flap.</p> <p><u>VELCRO CLOSURE:</u> Each pocket flap shall have a rectangular strip of Velcro tape measuring approximately 1" X 3/8" wide on each of the outer points. Velcro tape of the same size shall be properly positioned on the pockets to engage the tape on the flaps when closed.</p> <p><u>SEWING:</u> Collars, shoulder straps and flaps shall be single stitched 1/4" from the edge. The back yoke and joining seams shall be single-stitched on the edge. Sleeve insertion and side closing to be safety stitched. All sewing shall be of 100% Dacron matching thread.</p> <p><u>BUTTONS:</u> All buttons shall be made from thermo-setting polyester material and must match fabric.</p> <p><u>INTERLINING:</u> Collar and flaps to be interlined with Stabilized Mello-Press interlining.</p> <p><u>EMBLEM:</u> Shirts to have Birmingham Police Emblem attached to left sleeve and centered approximately one (1) inch below shoulder seam. Emblems to be furnished by the City of Birmingham to the successful bidder.</p> <p><u>SIZE MARKING:</u> Size and sleeve length shall be marked with indelible ink on a size loop attached to basic label in yoke and on outside of left front tail.</p> <p><u>PRESSING AND PACKING:</u> Shirts shall be carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts are to be shipped in strong boxes so as not to be damaged in shipment. Shirts to be packed twelve to a box with the same sizes marked on the outside of the box at one end.</p>		

SPECIFICATIONS FOR CITY OF BIRMINGHAM POLICE DEPARTMENT Men's winter shirts (long sleeve) Group 1	Bidder Complies	
	Yes	No
<p><u>STYLE:</u> It is the intention of this department to secure a tailored shirt equal in quality of workmanship, style and color to the shirt now on display as a sample. Sample shirt to be provided to lowest apparent bidder upon request.</p> <p>The style shall be cut on a form-fitting line with long sleeves and full-length tails. The shape of the pockets and general style will conform to the sample. The shirt to have two outside breast pockets and scalloped flaps having one button each. Also, to have full badge sling on left side and shoulder straps. The back to have a double yoke with High Lustre Venetian band and yoke trim.</p> <p><u>FABRIC:</u> Raeford Mills #3906-30 (Midnight Blue), 1 ply 75/25 Dacron Polyester/Worsted Wool Permanent Press in a tropical weave weighing 10 to 10-1/2 oz. per linear yard. Shoulder Straps shall be Color #3906-604, 75/25 Dacron Polyester/Worsted Wool Permanent Press in a tropical weave. (Lowest apparent bidder to supply verification of material style and color from Raeford Mills in letter form to the Police Department prior to shipment.)</p> <p><u>COLOR:</u> Midnight Blue. (Color MUST match that of sample shirt.)</p> <p><u>COLLAR:</u> Collar shall be one piece and to measure 3-1/4" long at points. The back of the stand is to measure 1-1/2". Collar to be top stitched 1/4" off the edge.</p> <p>The collar shall be made of four pieces; two pieces of self cloth, one whole lining and one piece of strip lining which is to be fused to the collar lining. Both pieces of lining to be fused to top collar. The collar shall be made with permanent collar stays. Stays to be attached to bottom collar.</p> <p>Innerstand and inner yoke to be made of matching 65% Dacron Polyester/35% Combed Cotton, poplin fabric.</p> <p><u>SHOULDER STRAPS:</u></p> <p>The shoulder straps shall be pointed at the end toward the neck of the shirt. The other end shall be sewn in sleeve head seam. The pointed ends shall be fastened with one matching button. The strap shall measure 2" at sleeve and tapered to 1-3/8". Straps are to be set approximately 1/2" from the collar. Shoulder straps shall be box-stitched to shoulders with row of cross stitching 2" from sleeve head seam and diagonally across from each end seam to the sleeve head seam.</p> <p><u>BADGE REINFORCEMENT:</u> Shall have a 2 ply sling-type badge reinforcement inside left front of shirt 1-1/8" wide to be centered and secured in left shoulder seam and left flap setting seam. Two buttonhole eyelets are to be spaced approximately 1-1/4" apart with the bottom eyelet approximately 1-1/4" from the top of the left pocket flap.</p> <p><u>FRONT:</u> Each front shall have a facing 3" in width extending from neckline to bottom of shirt provided by a turn-under of material. The left front shall also have a lined box pleat 1-1/2" wide finished, running full length of the shirt and shall be topstitched 1/4" from both edges.</p> <p>The left front shall have 7 buttonholes 3/4" from edge. Second buttonhole to be positioned 3" from top horizontal buttonhole, balance of buttonholes to be vertically spaced 3-1/2" apart on center. Buttons to be strongly attached through two thickness of material sewn on the right front and shall correspond to each buttonhole.</p> <p><u>PERMANENT CREASES:</u> Shall have five (5) permanent military creases using Lintrak method. Two creases on the front to be centered vertically through each pocket and flap and three creases on the back proportionately spaced.</p>		

SPECIFICATIONS FOR CITY OF BIRMINGHAM POLICE DEPARTMENT Men's winter shirts (long sleeve) Group 1	Bidder Complies	
	Yes	No
<p>LONG SLEEVES AND CUFFS: Sleeves are to be straight and whole with pleats and 5½” sleeve vent. Sleeve lengths must be available in lengths measuring 30” to 40” from center back of the shirt to the end of the sleeve cuff. Sleeve vent shall have a top facing approximately 1⅛” wide finished at the top with a neatly blocked point. Lower facing shall measure approximately ½” in width. Cuff to measure 2½” with rounded corners. There shall be two buttons with corresponding buttonholes on the cuff and one button with corresponding buttonhole in the sleeve vent facing.</p> <p>POCKETS: Shirt to have two (2) breast pockets with 1¼” stitched down pleat. Pocket to finish 5⅝” wide and 6” deep. The left breast pocket to have a pencil stitch approximately 1¼” wide.</p> <p>FLAPS: Pockets to have two (2) scalloped flaps, to finish 5¾” in length, 2¾” in width at center point and 2½” at sides. Flaps to be secured to front of shirt approximately ¼” above top of pocket. The left flap to have a pencil opening about 1¼” in width. A button is to be centered and secured ¾” above the center scalloped point on each flap.</p> <p>VELCRO CLOSURE: Each pocket flap to have a rectangular strip of Velcro tape measuring approximately 1” x ⅜” wide on each of the outer points. Velcro tape of the same size shall be properly positioned on the pockets to engage the tape on the flaps when closed.</p> <p>SEWING: All stitches must be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give the best durable press performance. Collars, shoulder straps and flaps shall be singled stitched ¼” from the edge. The back yoke and joining seams shall be single stitched on the edge. Sleeve insertion and side closing to be safety stitched. All sewing shall be of 100% Dacron matching thread.</p> <p>BUTTONS: All buttons shall be made from thermo-setting polyester material and must match fabric.</p> <p>INTERLINING: Collar and flaps to be interlined with Stabilized Mello-Press interlining.</p> <p>EMBLEMS: Shirts to have Birmingham Police Emblem attached to left sleeve and centered approximately one inch (1”) below shoulder seam. Emblems to be furnished by the City of Birmingham to the successful bidder.</p> <p>SIZE MARKING: Neck size and sleeve length shall be marked with indelible ink on a size loop attached to basic label in yoke and on outside of left front tail.</p> <p>PRESSING AND PACKING: Shirts shall be carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts to be shipped in strong boxes so as not to be damaged in shipment. Shirts to be packed twelve to a box with the sizes marked on the outside of the box at one end.</p> <p>SUCCESSFUL BIDDER SHALL FURNISH A WOMEN'S CUT LONG SLEEVE WINTER SHIRT EQUAL IN DESIGN TO THE SPECIFIED MEN'S LONG SLEEVE WINTER SHIRT.</p> <p>NOTE: Successful bidder shall furnish a pre-production sample in a ladies size 42 for inspection before full production begins.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specifications for men's trousers Group 2</p>	Bidder Complies	
	Yes	No
<p>It is the intention of this department to secure dress trousers equal in quality of workmanship, style and color to the trousers now on display as a sample.</p> <p>FABRIC: Raeford Mills, Style 573, Color 604, 55% Dacron Polyester/45% Wool. 11.5 to 12 oz. Gabardine. 3 ply warp and fill, thoroughly cold water shrunk. FABRIC IS TO HAVE RAEFORD MILLS RESTORA FINISH.</p> <p>DESIGN: Shall be made on a uniform pattern, having a plain front with quarter top pockets, a watch pocket and two (2) back pockets.</p> <p>POCKETS: The front pockets shall have a minimum opening of 6½” and they shall be 6” deep from the bottom of the opening. They will be stitched, turned, and re-stitched. The inside front pocket facing shall be a separate piece of self material finishing no less than 1¼” wide. The back pockets will have minimum opening of 5½” and will be 6” deep. They shall be made with a Reese PW automatic machine and finished on the outside with an exposed top and bottom cord. The left back pocket shall have a tab to button. The watch pocket, located approximately 2¾” to the front of the right side seam at the waistband, shall have an approximate opening of 2¾” and will be 3” deep. The front pockets and the watch pocket shall each have a straight bar-tack and each back pocket is to be <u>bar-tacked with a triangular bar-tacking machine.</u></p> <p>POCKETING: All pocketing shall be BLACK. Pocketing shall be 65% polyester/35% cotton with a minimum thread count of 68 x 54. The weight shall be 2.60 yd/lb.</p> <p>WASITBAND: The waistband shall be 2” wide and shall be closed with a crush-proof hook and eye, the eye being bar-tacked for stability. The waistband curtain, attached with a rocap machine, will have Snugtex and be made of black 65% polyester/35% cotton. No-roll waistband stiffener, ¾” in width, shall be sewn into the waistband on the front of the trouser from side seam to side seam. <u>STIFFENER SEWN INTO THE BACK OF TROUSER WAISTBAND WILL BE UNACCEPTABLE.</u> The trousers are to be made with a continuous closed waistband. The waistband shall be set on and shall be stitched below the lower edge through the outer fabric and the waistband curtain.</p> <p>INSIDE TRIM: The right fly and crotch linings shall be the same fabric and color as the waistband curtain. The right fly lining shall be sewn to the left fly below the zipper. The inside left fly shall be reinforced with Pellon. The crotch lining shall be serged to each front. <u>A separate French fly made of the outer fabric shall be sewn to the inside right fly. NO EXCEPTIONS TO THE SEPARATE FRENCH FLY.</u></p> <p>BELT LOOPS: There shall be a minimum of five (5) belt loops on waist sizes 28, 29, 30 and a minimum of seven (7) on all sizes over 30. Each loop is to be ¾” wide, of double thickness, and stitched on the face side with a 2-needle machine. Except for the back loop, which shall be tacked on, all loops will be sewn into the bottom of the waistband and into the rocap. They shall accommodate a 1⅝” wide belt.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specifications for men's trousers (cont'd) Group 2</p>	Bidder Complies	
	Yes	No
<p>ZIPPER: The trousers shall be closed with a heavy brass memory lock zipper and shall have a brass bottom stop at the base of the zipper chain. A straight bar-tack will be sewn through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape, the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bar-tack located below the bottom zipper stop on the inside of the trouser.</p> <p>SEAMING: The entire trouser is to be seamed with polyester core of 100% polyester spun thread. The seat seam shall be stitched with a tandem needle seat seaming machine.</p> <p>STRIPING: A 3/4" stripe, navy blue Tropical Raeford 3933-96, is to be sewn into seams. Stripe to extend to bottom of waistband. Inseam to be chain-stitched and seat seam to be chain-stitched with Tandem Needle Chain-stitched machine using heavy flexible thread. Stitching to be 1/16" apart. All seams to be pressed open.</p> <p>SIZE TAG: The trouser shall have a sewn in label with care and cleaning instructions and shall also have sewn in a permanent label showing the size of the trousers. Trousers shall have an outside waistband label which will be marked with lot number, size, fiber content and WPL number.</p> <p>FINISHING AND PRESSING: All loose threads shall be removed. Trousers must be pressed completely and properly with the side seam, inseam and set seam pressed open. There must be a Texpak clip attached to the top fly of the finished trouser.</p> <p>HEMMING AND ALTERATIONS: Vendor must be able to provide hemming and alteration services within the city limits of Birmingham during the hours of 8:00 a.m. until 5:00 p.m., Monday thru Friday. Trousers – waist, seat, length at no charge to the city at the time of purchase or initial issue to an officer by Police Distribution Center within a reasonable time thereafter. Charges for any other alterations will have to be approved by the appropriate department and billed separately.</p> <p>NOTE: Successful bidder shall furnish a pre-production sample in a men's waist size 36 for inspection before full production begins.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specifications for women's slacks Group 2</p>	Bidder Complies	
	Yes	No
<p>It is the intention of this department to secure dress slacks equal in quality of workmanship, style and color to the slacks now on display as a sample.</p> <p>GENERAL; Slacks shall match the men's trousers in construction and materials.</p> <p>FABRIC: Raeford Mills, Style 573, Color 604, 55% Dacron Polyester/45% Wool. 11.5 to 12 oz. Gabardine. 3 ply warp and rill, thoroughly cold water shrunk. FABRIC IS TO HAVE RAEFORD MILLS RESTORA FINISH.</p> <p>DESIGN: Shall be made on a modified ladies uniform pattern, having a plain front with quarter top front pockets and an elastic back.</p> <p>POCKETS: The front pockets shall have a minimum opening of 6½" and they shall be 5½" deep from the bottom of the opening. They will be stitched, turned, and re-stitched. The inside front pocket facing shall be a separate piece of self material finishing no less than 1¼" wide. The back pockets will have minimum opening of 5½" on size 14 and up and will be 6" deep on size 12 and under, minimum opening shall be 5" wide and 6" deep. They shall be made with a Reese PW automatic machine and finished on the outside with an exposed top and bottom cord. The front pockets shall each have a straight bar-tack and each back pocket is to be <u>bar-tacked with a triangular bar-tacking machine.</u></p> <p>POCKETING: All pocketing shall be BLACK. Pocketing shall be 65% polyester/35% cotton with a minimum thread count of 68 x 54. The weight shall be 2.60 yds./lb.</p> <p>WASITBAND: The waistband shall be 2" wide and shall be closed with a crush-proof hook and eye, the eye being bar-tacked for stability. The waistband curtain, attached with a rocap machine, will have Snugtex and be made of black 65% polyester/35% cotton. No-roll waistband stiffener, ¾" in width, shall be sewn into the waistband on the front of the trouser from side seam to side seam. <u>STIFFENER SEWN INTO THE BACK OF TROUSER WAISTBAND WILL BE UNACCEPTABLE.</u> The trousers are to be made with a continuous closed waistband. There shall be a special elastic back using the closed covered method. The relaxed finished waist measurement shall be 1½" smaller than the ticket size. The waistband shall be set on and shall be stitched below the lower edge through the outer fabric and the waistband curtain.</p> <p>INSIDE TRIM: The right fly and crotch linings shall be the same fabric and color as the waistband curtain. The right fly lining shall be sewn to the left fly below the zipper. The inside left fly shall be reinforced with Pellon. The crotch lining shall be serged to each front. <u>A separate French fly made of the outer fabric shall be sewn to the inside right fly. NO EXCEPTIONS TO THE SEPARATE FRENCH FLY.</u></p> <p>BELT LOOPS: There shall be a minimum of five (5) belt loops on waist sizes 12 and under and a minimum of seven (7) on all sizes over 14. Each loop is to be ¾" wide, of double thickness, and stitched on the face side with a 2-needle machine. Except for the back loop, which shall be tacked on, all loops will be sewn into rocap at the top and dropped and tacked below the waist seam. They shall accommodate a 1⅝ wide belt.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specifications for women's slacks Group 2</p>	Bidder Complies	
	Yes	No
<p>ZIPPER: The trouser shall be closed with a heavy brass memory lock zipper and shall have a brass bottom stop at the base of the zipper chain. A straight bar-tack will be sewn through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape, the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bar-tack located below the bottom zipper stop on the inside of the trouser.</p> <p>SEAMING: The entire trouser is to be seamed with polyester core of 100% polyester spun thread. The seat seam shall be stitched with a tandem needle seat seaming machine.</p> <p>STRIPING: A ¾" stripe, navy blue Tropical Raeford 3933-96, is to be sewn into seams. Stripe to extend to bottom of waistband. Inseam to be chain-stitched and seat seam to be chain-stitched with Tandem Needle Chain-stitched machine using heavy flexible thread. Stitching to be 1/16" apart. All seams to be pressed open.</p> <p>SIZE TAG: The trouser shall have a sewn in label with care and cleaning instructions and shall also have sewn in a permanent label showing the size of the trousers. Trousers shall have an outside waistband label which will be marked with lot number, size, fiber content and WPL number.</p> <p>FINISHING AND PRESSING: All loose threads shall be removed. Trousers must be pressed completely and properly with the side seam, inseam and set seam pressed open. There must be a Texpak clip attached to the top fly of the finished trouser.</p> <p>HEMMING AND ALTERATIONS: Vendor must be able to provide hemming services within the city limits of Birmingham during the hours of 8:00 a.m. until 5:00 p.m., Monday thru Friday. Trousers – waist, length at no charge to the city at the time of purchase or initial issue to an officer by Police Distribution Center within a reasonable time thereafter. Charges for any other alterations will have to be approved by the appropriate department and billed separately.</p> <p>NOTE: Successful bidder shall furnish a pre-production sample in a ladies waist size 16 for inspection before full production begins.</p>		

CITY OF BIRMINGHAM POLICE DEPARTMENT		Bidder Complies	
Specification for Spiewak Style S578V or equal Safety Shell Parka Group 3		Yes	No
Heat: Hot Pressing Test Method AATCC 133			
Dry Pressing @ 110o C Fluorescent Yellow	5.0		
Dry Pressing @ 150o C Fluorescent Yellow	5.0		
Dry Pressing @ 200 C Fluorescent Yellow	4.5		
Key to AATCC Gray Scale Rating (applies to all above)			
Class 5 – Negligible or no color alteration			
Class 4 – Slight color change			
Class 3 – Noticeable color change			
Class 2 – Considerable color change			
Class 1 – Much color alteration			
Dimensional Change of Background Material			
The dimensional change of background material shall not exceed +/- 4% in length and +/- 2% in width.			
Test Method AATCC 135-1995 (3) IIIA (iii)			
Machine Wash @ 105° F Permanent Press Cycle / Tumble Dry Perm. Press Cycle			
Fluorescent Yellow			
Length	0.6%	4.0% max.	
Width	0.6%	2.0% max	
Test Method AATCC 96 IIIe-A			
Commercial Laundering @ 145° F Tumble Dry			
Fluorescent Yellow			
Length	1.1%	4.0% max.	
Width	0.7%	2.0% max	
Determination of Color – ANSI 107-2004			
The color shall be measured in accordance with the procedures defined in ASTM E1164-94 with polychromatic illumination D65 and 45/0 (0/45) geometry and 2o standard observer. The specimen shall have a black underlay with a reflectance of less than 0.04.			
VizMax™ Performance Fabric			
Composition: 36% Polyurethane/64% Polyester			
Property	Units	Typical Value	Method
Weight	gsm	180	BS3424pt1
Width	cms	148	BS3424pt1
Tensile Strength N/50mm		Warp 1050	BSENISO1421
		Weft 850	
Tear Strength	Newtons	Warp 45	BS3424pt5
Tongue		Weft 45	
Hydrostatic Head Kpa	as rec	>30	BS3424pt26
	After wash	>30	
	After Flex	>30	
Breathability	%	80	BS7209
Water Vapor	Pa/W	Rct7m2	DIN EN 31 092

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specification for Spiewak Style S578V or equal Safety Shell Parka Group 3</p>	Bidder Complies	
	Yes	No
<p>Care Instructions: Wash at 40° Celsius, wool cycle. Do not tumble dry. Iron at Cool Setting (Fabric Side). Do not fold away wet. Do not bleach. Use mild soap.</p> <p>Reflective Tape There shall be 2-inch wide 3M 8906 silver reflective tape sewn to the shell for visibility and safety of wearer. The reflective properties of the reflective tape and configuration shall meet and exceed the EN-471 and ANSI 107-2004 Class 3 minimum requirements. The placement configuration shall consist of two horizontal bands of reflective tape on the body and on the sleeves.</p> <p>Front The parka shall have a front #8 Delrin 2-way zipper that shall extend to the edge of the collar. The front zipper shall measure approximately 29 ½” long (size large/regular). There shall be an outside windfly of self-goods which measures approximately 29 ½” long by 3” wide (large/regular). The fly shall close with 7 snaps with the female snap side located on the underside of the outer flap. The 5 bottom fly snaps shall be placed approximately 5 ¾” center to center apart from each other with the bottom snap starting approximately 1 ½” from the bottom of the windfly. The upper 2 snaps shall be spaced approximately 2 ¾” center-to-center for proper closure of the stand up collar. The parka shall have a rain shed shoulder yoke measuring approximately 7” down the front and 6” down the back (from the high point shoulder). The parka shall feature snow proof-covered pockets that shall be lined front and back with 220-gram Microfleece. The pocket flaps shall measure approximately 2 ½” at their peak closest to the zipper and shall gradually increase in width until the side seam at which point the flaps shall measure approximately 4”. The pocket flap shall measure approximately 8 ½” in width. There shall be a bar tack midway down the pocket flap on the zipper side to secure the flap. The front length shall measure approximately 30” (Large-Regular). There shall be a badge tab made of self-fabric measuring 3 ¼” x 7/8”. It shall be swift tabbed into the jacket pocket for optional sew on by wearer. There shall be a mic tab made of self-fabric on the left and right shoulders.</p> <p>Back The back shall be extended approximately 3 ½” inches from the front for additional protection and shall be well rounded and symmetrical on both sides. This extension shall incorporate a fully enclosed elastic shock cord with no loose ends that can be cinched using a tension-loaded barrel lock on either side. The back length shall measure approximately 32 ½” (size large/regular). The inside of the extension flap shall have a #5 nylon coil 22” zipper for access to the shell fabric for customization after production.</p> <p>Customization There shall be two lines of heat applied, black lettering; the font shall be Helvetica Neue 87 Heavy Condensed. The lettering shall measure 6.375" high x 14" wide and placed centered on the upper back between shoulder blades. The lettering shall read:</p> <p style="text-align: center;">BIRMINGHAM POLICE</p> <p>Sleeves The sleeves shall be 2-piece coat style construction finished with a ½ elasticized 2” cuff with a snap tab closure. There shall be 3 high compression snaps for cuff adjustment. The snap tab closure shall be made of self-goods approximately 3 ¼” long X 1” wide tapering to the bottom snap head. The under sleeves shall feature ventilating pit-zips with #5 delrin zippers that measure approximately 12” long. The pit-zips shall be covered with a welt of shell material 12” long X ½” wide.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specification for Spiewak Style S578V or equal Safety Shell Parka Group 3</p>	Bidder Complies	
	Yes	No
<p>Collar and Hood The stand up collar shall measure approximately 4” in height and be well shaped and symmetrical. There shall be a #3 nylon coil zipper measuring approximately 8 ½” long sewn approximately 2 ¼” from the top of the collar that shall hide the drop-in 3-piece waterproof hood. There shall be a Val cover over the zipper. The side panels of the hood shall measure approximately 11 ½” in height X 8” in width. The middle piece of the 3 piece hood shall measure approximately 4 ½” wide and be sewn single needle raised. The hood shall be shaped to allow peripheral vision. The hood shall be finished with elastic shock cords with bell-shaped cord locks for proper adjustment.</p> <p>Inside Detail The parka lining shall be 100% 210T nylon taffeta with acrylic coating 300mm - 450mm. There shall be a left inside welt pocket that measures approximately 9” wide X 9” deep. The pocket shall close with a ½” piece of black power hook and loop fastener that shall be centered on the top of the pocket welt. Behind the inside pocket there shall be an 8” nylon coil zipper on a facing of shell material for access to the outer shell for customization to the left front without sewing through the lining. There shall be a patch pocket of shell material on the right side with a vertical 7” nylon coil zipper closure measuring approximately 6 1/2” wide X 8” high. The parka shall contain a tunneled draw cord. The draw cord shall be placed approximately 20” from the top of the front zipper. There shall be a hangar braid of self-fabric sewn into the inside collar.</p> <p>Side Vents There shall be 2 side vent nylon coil zippers measuring approximately 10” to allow access to equipment and placed on either side at end of the parka. There shall be a snap tab strap measuring approximately 3” long and placed at the bottom of each side vent zipper and equipped with high compression snaps and designed to provide a tab that snaps across zippers to prevent movement of side vents when unzipped.</p> <p>Sizes Regular: S – 5XL Long: M – 5XL</p> <p><u>REQUIREMENTS</u> All documentation listed below must be provided at the time of the bid opening and dated prior to the bid opening date. Failure to provide any and all documentation may result in rejection of bid.</p> <p>1. Finished garments based on a size small/regular are to be third party tested by an accredited laboratory, and the results must be dated prior to bid opening date and must be submitted with bid.</p> <p>2. Manufacturer must be ISO 9001: 2000 certified and a copy of certificate must be included with bid and certificate must be dated prior to the bid opening date.</p> <p>3. A sample, size Medium, is required at the time of bid opening.</p> <p>4. Third party independent test results must be submitted on the background fabric and retro-reflective tape dated prior to the bid opening date and submitted with bid. All ANSI documents and test results must be in ANSI 107-2004 format (this includes reflective tape, fabric, and ANSI garment style certificate).</p>		

CITY OF BIRMINGHAM POLICE DEPARTMENT Specification for Spiewak Style S578V or equal Safety Shell Parka Group 3	Bidder Complies	
	Yes	No
<p>5. Successful bidder must provide third party independent test reports showing that the following components meet the written spec:</p> <p>Outer shell Fabric Reflective tape Zippers Snaps Shell/pocket lining fabric Hook & loop</p> <p>6. Garment must be a stock, off the shelf item. Successful bidder must provide at least 10 agencies of 250 personnel or larger that are currently using the product submitted. Bidder must provide the agency name, contact, and telephone number.</p> <p>7. Manufacturer must have, and submit, a published lifetime warranty or limited lifetime warranty against product defects, component failure, and waterproofness. No special warranties shall be accepted for this specification.</p> <p>8. Item bid shall be a stock product and must be available for viewing by agencies and must be published in a bound 2009 catalog.</p>		

CITY OF BIRMINGHAM POLICE DEPARTMENT Specification for Spiewak Style S1785 or equal Tactical Waterproof Pant Group 3		Bidder Complies																																																	
		Yes	No																																																
<p>GENERAL DESIGN The Tactical pant shall be waterproof/windproof and breathable. It is designed to be worn as an over pant and must present a clean image when worn and shall not impede mobility of the wearer as per design.</p> <p>COLOR Black (003)</p> <p>OUTER SHELL The shell fabric shall be Real Tactel™, 4 -ply air texturized 100% nylon with a durable water repellent finish and back coating. The back coating shall be PU coated w/p 2000mm. Yarn size shall be N/F 70 D/34F x N/ATY 240 D/FD, Density shall be 156 x 52, Weight shall be 172 g/yd. The shell fabric shall also meet the following requirements:</p> <p>Shell Fabric Requirements and Verification</p> <table border="1"> <thead> <tr> <th></th> <th>Test Method</th> <th>Requirement</th> </tr> </thead> <tbody> <tr> <td>Weight, g/yd (minimum)</td> <td>ASTM D3776, Opt C</td> <td>168 g/yd</td> </tr> <tr> <td>Tensile Strength (Minimum pounds)</td> <td>ASTM D5034 C.R.E Grab Method</td> <td>Warp 615 Fill 1000</td> </tr> <tr> <td>Tear Strength (minimum grams)</td> <td>ASTM D1424 Pendulum Method</td> <td>Warp 10.5 Fill 29</td> </tr> <tr> <td>Abrasion Resistance Applied pressure 9kPa, Multidirection, end point when two threads were broken</td> <td>ASTM D 4966 Martindale Method</td> <td>20000<</td> </tr> <tr> <td>Seam Slippage</td> <td>ASTM D 434 C.R.E.</td> <td>Warp: S.O1/4" – NIL 71 (STB) Fill S.O ¼" – NIL 95 (STB)</td> </tr> <tr> <td>Spray Rating</td> <td>AATCC 22</td> <td>100, 100, 100</td> </tr> <tr> <td>Dimensional Stability, (maximum %) after 5 cycles</td> <td>AATCC 135 Test (3)IV(A)ii</td> <td>Warp 3.0 Fill 3.0</td> </tr> </tbody> </table> <p>SHELL LINING The lining shell fabric shall be 100% nylon 210T, 50 denier/72 filament warp and fill, with a nominal weight of 3.1 (± 0.1) oz/yd². The yarn count shall be 166 x 104 (± 2 ypi). The color shall be black.</p> <p>Waterproof/breathable Barrier Membrane MUST MEET OR EXCEED THE FOLLOWING SPECIFICATION</p> <table border="1"> <thead> <tr> <th>Property (U.S. units)</th> <th>Nominal Values (SI units)</th> <th>Nominal Values (SI units)</th> <th></th> </tr> </thead> <tbody> <tr> <td>Finished Fabric Wt.</td> <td>2.67 –3.5 (oz/yd squared)</td> <td>92-120 (g/m squared)</td> <td>ASTM D3776-96</td> </tr> <tr> <td>Tensile Strength</td> <td>Warp</td> <td>30(lbf)</td> <td>135 N</td> </tr> <tr> <td>Fill</td> <td>30(lbf)</td> <td>135 N</td> <td></td> </tr> <tr> <td>Trap Tear</td> <td>Warp:</td> <td>8 lbf</td> <td>36 N</td> </tr> <tr> <td></td> <td>Fill:</td> <td>8 lbf</td> <td>36 N</td> </tr> </tbody> </table>					Test Method	Requirement	Weight, g/yd (minimum)	ASTM D3776, Opt C	168 g/yd	Tensile Strength (Minimum pounds)	ASTM D5034 C.R.E Grab Method	Warp 615 Fill 1000	Tear Strength (minimum grams)	ASTM D1424 Pendulum Method	Warp 10.5 Fill 29	Abrasion Resistance Applied pressure 9kPa, Multidirection, end point when two threads were broken	ASTM D 4966 Martindale Method	20000<	Seam Slippage	ASTM D 434 C.R.E.	Warp: S.O1/4" – NIL 71 (STB) Fill S.O ¼" – NIL 95 (STB)	Spray Rating	AATCC 22	100, 100, 100	Dimensional Stability, (maximum %) after 5 cycles	AATCC 135 Test (3)IV(A)ii	Warp 3.0 Fill 3.0	Property (U.S. units)	Nominal Values (SI units)	Nominal Values (SI units)		Finished Fabric Wt.	2.67 –3.5 (oz/yd squared)	92-120 (g/m squared)	ASTM D3776-96	Tensile Strength	Warp	30(lbf)	135 N	Fill	30(lbf)	135 N		Trap Tear	Warp:	8 lbf	36 N		Fill:	8 lbf	36 N
	Test Method	Requirement																																																	
Weight, g/yd (minimum)	ASTM D3776, Opt C	168 g/yd																																																	
Tensile Strength (Minimum pounds)	ASTM D5034 C.R.E Grab Method	Warp 615 Fill 1000																																																	
Tear Strength (minimum grams)	ASTM D1424 Pendulum Method	Warp 10.5 Fill 29																																																	
Abrasion Resistance Applied pressure 9kPa, Multidirection, end point when two threads were broken	ASTM D 4966 Martindale Method	20000<																																																	
Seam Slippage	ASTM D 434 C.R.E.	Warp: S.O1/4" – NIL 71 (STB) Fill S.O ¼" – NIL 95 (STB)																																																	
Spray Rating	AATCC 22	100, 100, 100																																																	
Dimensional Stability, (maximum %) after 5 cycles	AATCC 135 Test (3)IV(A)ii	Warp 3.0 Fill 3.0																																																	
Property (U.S. units)	Nominal Values (SI units)	Nominal Values (SI units)																																																	
Finished Fabric Wt.	2.67 –3.5 (oz/yd squared)	92-120 (g/m squared)	ASTM D3776-96																																																
Tensile Strength	Warp	30(lbf)	135 N																																																
Fill	30(lbf)	135 N																																																	
Trap Tear	Warp:	8 lbf	36 N																																																
	Fill:	8 lbf	36 N																																																

CITY OF BIRMINGHAM POLICE DEPARTMENT			Bidder Complies	
Specification for Spiewak Style S1785 or equal Tactical Waterproof Pant Group 3			Yes	No
Barrier Membrane Material:				
The Barrier membrane shall be 2 layers: The top layer shall be 100% polyester 50 denier micro-fiber cloth, 72 filament warp and fill, with a nominal weight of 2.7 oz/yd ² . The yarn count shall be 104 x 62 ± 2 yarns per inch. The bottom layer shall be 100% polyester non-porous film with built in hydrophilic molecular zones.				
Lining shall have the following minimum physical properties:				
CHARACTERISTIC	REQUIREMENT	TEST METHOD		
Moisture Vapor Transmission Rate (g/m squared/24hr) Procedure B Procedure BW	500 Minimum 4000 Minimum	ASTM E 96-93 <u>1</u> / ASTM E 96-93 <u>2</u> /		
Hydrostatic Resistance (psi)	100 Minimum	FED-STD-191A 5512 <u>3</u> /		
After 10 Laundry Cycles	No leakage	FED-STD-191A 5516 <u>4</u> /		
After 10 Dry Clean Cycles	No leakage	FED-STD-191A 5516 <u>4</u> /		
After 10 Laundry Cycles	No leakage	FED-STD-191A 5516		
After 10 Dry Clean Cycles	No leakage	FED-STD 191A 5516		
BODY DETAIL				
The front closure of the pant shall be as spring loaded compression snap with a waterproof zippered front. The black waterproof front zipper shall measure approximately 7" long. The waistband shall be approximately 1 3/4" high. The inside of the waistband will feature a 1" black gripper waistband that will be approximately 2 1/2" from the center of the female snap and approximately 2 3/4" from the male snap. There will also be an elasticized shock cord with a double eyelet on each side to form a self-contained shock cord with a ball and channel stopper. The first eyelet on the wearer's inside right shall be placed approximately 1 1/4" from the center of the male snap. The second eyelet shall be 1" center to center from the first eyelet. The eyelets on the wearer's left shall be placed approximately 3/4" from the female snap. These eyelets shall also be spaced 1" center to center. All eyelets shall be oxidized black metal eyelets. In addition the back of the waistband shall be elasticized. There shall be 5 keeper belt loops on the front of the waistband. The belt loops shall measure 1" wide by 8" long. The belt loops shall be sewn on the top of the waistband and approximately 1/4" below the waistband. Each belt loop will close with power hook and loop. The loop shall be on the inside top portion of the keeper and shall measure approximately 2" long x 1" wide. The hook shall be on the outside portion of the lower keeper and shall measure approximately 1" x 2". Two of the keepers shall be placed on the front of the waistband. The left side keeper shall be placed approximately 3 1/2" from the closed snap. The right side keeper shall be placed approximately 5" from the closed snap. There shall be 3 keeper belt loops on the back of the pant. The center keeper shall be placed in alignment with the back seam of the pant. The keepers to the right and left of the back center keeper will be spaced 6 1/4" with the elastic stretched. The front rise seam shall measure approximately 14" long. The back rise including waistband shall measure 17 1/2" long. The pant out seam including waistband shall measure 44" long. The pant inseam shall measure 32" long (size Large/Regular). Each pant leg shall close with an 18" waterproof black zipper. There shall be one spring loaded compression snap approximately 10" from the bottom of the pant leg. There shall be a 1" Val cover of self-fabric that covers the waterproof zipper. The pant bottom shall finish with a 1" elasticized cuff. There shall be a self-fabric tab that measures 3 1/2" long x 1" wide and features a female snap placed approximately 3" from the end of the tab. The female snap shall seal the pant by attaching to one of two male compression snaps. Those snaps are placed approximately 1 1/2" apart with the first snap approximately 1 3/4" from the edge of the pant.				

<p align="center">CITY OF BIRMINGHAM POLICE DEPARTMENT Specification for Spiewak Style S1785 or equal Tactical Waterproof Pant Group 3</p>	Bidder Complies	
	Yes	No
<p>POCKETS There shall be 2 waterproof front zippered pockets. The pockets shall begin approximately 2” from the bottom of the waistband and be cut into the side seams. The pockets shall have a bar tack reinforcement at both the top and the bottom of the pockets. The pockets shall feature a ¾” Val cover over the zipper. The zipper opening shall be a #5 Nylon coil zipper and shall measure approximately 8” long. The front pocket shall run from the waistband to the top of the cargo. There shall be two waterproof back pockets shall be place 3 1/8” below the waistband and 2 ½” from the side seam. The back pocket shall be a welt pocket measuring approximately 6 ½” long x ¾” high. The welt shall be bar tacked at each end of the welt covering. There shall be a #5 nylon coil zipper closure on the back welt pocket measuring approximately 6” long.</p> <p>There shall be a zipper pull made of self-fabric attached to the metal zipper pull for easy closure of the pocket.</p> <p>SEAM SEALING TAPE The tape for covering and sealing all seams and stitching through the polyester lining fabric shall be 1 inch wide. The sealing tape shall be a thermoplastic polyurethane adhesive tape. The adhesive for the seam sealing tape shall be made in sufficient thickness to match the laminate performance requirements under the Table for Middle Layer (membrane).</p> <p>SNAPS All snaps shall be 24 ligne, oxidized, high compression snaps with an anodized cap.</p> <p>SIZES Regular dimension: Small – 5XL Long dimension: Medium – 5XL</p> <p>CARE Each garment shall have sewn in cloth certification, size, and care and content labels with permanent embroidery that shall not transfer color. The labels shall be legible for the life of the garment.</p> <p>NOTE The following requirements are to be supplied at the time of the bid opening date. Failure to do so may result in rejection of the bid.</p> <p><u>ADDITIONAL REQUIREMENTS:</u> Failure to provide any of the following will be cause for rejection.</p> <p><u>ISO 9001:2000 Certification:</u> Manufacturer must be ISO 9001:2000 Certified and must submit a copy of the certification with their bid. Certificate must be dated prior to the bid opening date.</p> <p><u>Manufacturer References:</u> Bidders are to supply with their bid a letter from the manufacturer of the garment bid and include contact names, addresses, and phone numbers for a minimum of 10 agencies that have at least 250 uniformed personnel in the US who are currently purchasing the product submitted.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT Specification for Spiewak Style S1785 or equal Tactical Waterproof Pant Group 3</p>	Bidder Complies	
	Yes	No
<p><u>Certification/Verification Documents:</u> Successful bidder must provide third party documentation (as specified) from an accredited independent third party lab or a certificate from the mill/converter/manufacturer with their bid that proves that the variation(s) meets or exceeds the required performance of the components, design, and construction required in this specification. A third party lab is defined as a lab in which neither the manufacturer nor bidder has any ownership or interest and for which the relationship between the two companies is strictly a customer-provider relationship. All third party lab documents must show the results using the test methods as specified in the details of this bid document. Certification from mill/converter/manufacturer must be on that supplier's (NOT THE BIDDER'S) letterhead or official form with company address and phone number and must include the manufacturer's part number. All test reports must be dated prior to bid release date and must at a minimum address the following components:</p> <ul style="list-style-type: none"> A. Basic Shell Fabric B. Middle Layer (membrane) C. Lining Shell Fabric D. Zippers E. Snaps <p><u>WARRANTY:</u> Manufacturer must provide a published lifetime or limited lifetime warranty against product defects, component failure, and waterproofness. There will be no special warranties accepted for this specification.</p> <p>A sample, size Medium, is required at the time of bid opening.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT JAIL DRESS UNIFORMS GROUP 4</p>	Bidder Complies	
	Yes	No
<p>Long Sleeve Dac/Cotton Shirt</p> <p>Material: 65% Dac Polyester, 35% Combed Cotton. Military Creases sewn in, three (3) down back and one (1) down each front Scalloped pocket flaps with velcro closures</p> <p>Color: White or Grey</p> <p>Creasing The collar is to be die cut. The back of the stand is to measure 1-1/2". The points, widespread, are to be 3-1/4" in length and top stitched 1/4" from edge. The interlinings are to be 100% polyester taffeta Permanent collar stays of proper length (3-1/4"), are to be sewn inside collar so that no stitches are made through bottom leaf. The stand shall fasten with one (1) button.</p> <p>Sleeves: To be straight and whole. There shall be one (1) button placed on sleeve placket approximately 2-1/2" above the top of the cuff. The top of the cuff shall be 2-1/2" wide and shall be top stitched 1/4" around the edge of the cuff. Cuff will close with two (2) buttons. Sleeves must be secured to the body of the shirt by means of a narrow stitch with a safety stitch so as to strengthen the seam. The same stitch must be used on the side closing seam as well. Emblem (furnished by the City) to be sewn on left sleeve.</p> <p>Front: The front shall have a center facing 1-1/2" wide extending from collar stand to bottom of shirt and be made of same materials as shirt fabric, with a 100% polyester interlining. There shall be two (2) rows of stitching 3/4" apart. The button stand, 3/8" wide, shall be self lined and placed on the right side extending from collar stand to bottom of shirt. Buttons shall be securely attached to the button stand and shall correspond to the buttonholes on the interfacing. There will be one (1) military crease sewn in each front.</p> <p>Pockets: To have two (2) breast pockets with bellows in center and with mitred corners to finish 5-3/8" wide and 6" long. The left breast pocket to have a pencil opening about 1-3/8" in width. Velcro 1/2" wide and 1" long to be placed on edges on each pocket to secure velcro placed on corners of each flap.</p> <p>Flaps: To have scalloped flaps to finish 5-1/2" in width and 2-3/4" in length at the center and each side. Flaps to be secured to front of shirt approximately 1/4" above top of pocket. The left flap to have a pencil opening about 1-3/8" in width. Velcro to be placed on corners of each flap. Collar stays placed in corners of each flap to prevent curling.</p> <p>Badge Patch: Inside sling type badge holder of self-goods approximately 1-1/2" wide to extend from joining seam to pocket of left front. Two (2) small buttonholes 1-1/4" apart with lower buttonhole approximately 3/4" above the flap.</p> <p>Shoulder Straps: The shoulder straps shall be pointed at the end toward the neck of the shirt. The other end shall be sewn in sleeve head seam. The strap shall measure 2" at sleeves and taper to 1-1/2". Straps are to be set about 1/2" from the collar. Shoulder straps shall be "X" stitched to shoulders with a row of cross stitching 2" from sleeve head seam. The "X" stitching shall extend diagonally from each end of the cross stitch to the sleeve head seam.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT JAIL DRESS UNIFORMS GROUP 4</p>	Bidder Complies	
	Yes	No
<p>Collar Stays: The collar stays shall be of good quality staler vinyl, of proper length.</p> <p>Interlinings: Collar and center facing will be of 100% polyester interlining.</p> <p>Size Marking: Size tab to be sewn in with label to the inside yoke of shirt.</p> <p>Buttons: All buttons shall be made from thermosetting polyester material and must match the fabric.</p> <p>Pressing and Packing: Shirts shall be carefully pressed by hand in a first class manner. Shirts to be shipped in strong boxes so as not to be damaged in shipment. Shirts to be packed in individual polyethylene bags. Shirts to be Southeastern 3103 (white) or Southeastern 3106 (grey) or equal or better.</p> <p>Alternate: Same as above except with the addition of a zipper to the front of the shirt. Zipper to be added by a shirt maker.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT JAIL DRESS UNIFORMS GROUP 4</p>	Bidder Complies	
	Yes	No
<p>Short Sleeve Dac/Cotton Shirt</p> <p>Military crease shirt with scalloped pocket flaps and sewn in velcro closures</p> <p>Color: White or Grey</p> <p>Material: Spring Mills 65% dacron polyester,35% combed cotton, weight 4.5 oz. per yard</p> <p>Creasing: Pockets and pocket flaps to be die creased to give uniform shape and size. The shirt is to have sewn in permanent military creases, 2 in front, 3 in back.</p> <p>Collar: The collar is to be die cut. Convertible collar is to measure 3-1/4" long at points and top stitched 1/4" from edge. The interlinings are to be 100% polyester. Permanent collar stays of proper length are to be sewn inside the collar so that no stitches are made through the bottom leaf.</p> <p>Sleeves: Sleeves are to be straight and whole, have a 1/2" hem and finish 9-1/2" long from the shoulder seam. The sleeves must be secured to the body of the shirt by means of a narrow stitch with a safety stitch so as to strengthen the seam. The same stitch must be used on the side closing seam as well. The sleeve seam is to be bar tacked at the bottom of the hem for strength. Emblem (furnished by the City) to be sewn on left sleeve.</p> <p>Front: Right front shall have a facing 3" in width extending from neckline to bottom of shirt provided by a turn-under of the material. The left front shall have 7 buttonholes 3/4" from edge, 3-1/2" apart. Buttons to be strongly attached through two thickness of material forming right front and shall correspond to each buttonhole. Left front also to have mock pleat 1-1/2" wide down face of front.</p> <p>Pockets: To have two (2) breast pockets with mitered corners to finish 5-3/8" wide and 6" long. The left breast pocket to have a pencil opening about 1-3/8" in width. Both pockets to have a 1-1/2" box pleat stitched top and bottom to prevent spreading. Velcro 1/2 wide and 1" long to be placed on edges on each pocket to secure velcro placed on corners of each flap.</p> <p>Flaps: To have scalloped flaps to finish 5-1/2" in width and 2-3/4" in length at the center and each side. Flaps to be secured to front of shirt approximately 1/4" above top of pocket. The left flap to have a pencil opening about 1-3/8" in width. Velcro to be placed on corners of each flap. Collar stays placed in corners of each flap to prevent curling.</p> <p>Badge Patch: Inside sling type badge holder of self goods approximately 1-1/2" wide to extend from joining seam to pocket of left front. Two (2) small buttonholes 1-1/4" apart with lower buttonhole approximately 3/4" above flap.</p> <p>Shoulder Straps: The shoulder straps shall be pointed at the end toward the neck of the shirt. The other end shall be sewn in sleeve head seam. The strap shall measure 2" at sleeve and taper to 1-1/2". Straps to be set 1/2" from the collar. Shoulder straps shall be "X" stitched to shoulders with a row of cross stitching 2" from sleeve head seam. The "X" stitching shall extend diagonally from each end of the cross stitch to the sleeve head seam.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT JAIL DRESS UNIFORMS GROUP 4</p>	Bidder Complies	
	Yes	No
<p>Collar Stays: The collar stays shall be good quality staler vinyl, of proper length.</p> <p>Interlinings: Collar and center facing will be of 100% polyester interlining</p> <p>Size Marking: Size tab to be sewn in with label to the inside yoke of the shirt.</p> <p>Buttons: All buttons shall be made from thermosetting polyester material and must match the fabric.</p> <p>Shirts to be Southeastern 3203 (white) or 3206 (grey) or equal or better.</p> <p>Alternate: Same as above except with the addition of a zipper to the front of the shirt. Zipper to be added by shirt maker.</p>		

CITY OF BIRMINGHAM POLICE DEPARTMENT JAIL DRESS UNIFORMS GROUP 4	Bidder Complies	
	Yes	No
<p>Trousers</p> <p>Fabric: From Graniteville, style Super 2020, 65% polyester/35% cotton 7.75 oz. 2 X 1 left hand twill</p> <p>Color: Navy</p> <p>Design: The front shall be plain with two (2) full quarter top front pockets and two (2) back pockets.</p> <p>Pockets: The front pocket opening will be a minimum 6" and be 6" deep from the bottom of the opening. They shall be stitched, turned, and re-stitched. The inside front pocket facing shall be a separate piece of self material finishing no less than 1-1/2" wide. The back pockets will have a minimum opening of 5-1/4" and be 6" deep, and be made with a Reese PW automatic machine, finished on the outside with an exposed top and bottom cord top stitched. Facing shall be of self material and measure no less than 1-1/2". The left back pocket shall have a tab to button. The front pockets and the back pockets shall be bar tacked with a triangular bar tacking machine.</p> <p>Pocketing: The pocketing shall be black, 75% polyester 25% cotton, minimum thread count of 86 X 56. The weight shall be 3.0 yd/lb. All pocketing shall harmonize with outer fabric.</p> <p>Waistband: The waistband shall be 2" wide and shall be closed with a crushproof hook and eye being bar tacked for stability. The waistband curtain, attached with a rocap machine, shall have snugtex and be made of black 75% polyester/25% cotton. Banrol waistband stiffener, 3/4" in width shall be sewn into the waistband on the front of the trouser from side seam to side seam. The trousers are to be made with a continuous waistband.</p> <p>Inside Trim: The right fly shall be the same fabric and color as the waistband curtain. The right fly lining shall be sewn to the left fly below the zipper. The inside left and right flies shall be fused with interlining for stability. A separate french fly made of the outer fabric shall be sewn to the inside right fly.</p> <p>Belt Loops: There shall be a minimum of five (5) belt loops. Each loop shall be 3/4" wide of double thickness and stitched on the face side with a needle machine. Except for the center loop, all loops shall be sewn into the center of the waistband and into rocap and bar tacked 1/4" below waistband as to accommodate a 2" belt.</p> <p>Zipper Closure: Trousers shall be closed with a YKK brass zipper which has a brass bottom stop at the bottom of the zipper chain and a brass ratcheting semi-auto lock slider. A straight bar tack shall be sewn through from the bottom of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape, the right and left fly lining. Right and left fly shall be joined by an additional bar tack located below the bottom zipper stop on the inside of the trouser.</p> <p>Seaming: The entire trouser is to be seamed with polyester core thread. The rear seam shall be stitched with a tandem needleseat seaming machine. All exposed inside seams of the trouser are to be serged.</p> <p>Pressing and Finishing: Trousers must be properly pressed on hot head presses and properly shaped. The outseam and inseam must be pressed open.</p>		

<p style="text-align: center;">CITY OF BIRMINGHAM POLICE DEPARTMENT JAIL DRESS UNIFORMS GROUP 4</p>	Bidder Complies	
	Yes	No
<p>Labels: The trousers must have a care label permanently affixed and must also have size label showing fiber content and WPL number.</p> <p>Striping: For officers gold stripe sewn into the seam from the waistband down. Bidders are to average cost items to come up with a single unit price for each line item.</p> <p>Trousers to be Southeastern 3001 or equal or better.</p> <p style="text-align: center;">Bendover Necktie Metal Clip</p> <p>Necktie: 100% polyester pattern, fully lined, bar-tacked at both ends, fore-in-hand french cuff ends, and clip on style. Finished length from top of knot to tip of tie 17" to 17-1/2", width at widest point 3-1/4".</p> <p>Color: Black</p> <p>Belts: To be top grain black leather 1-3/4" wide with silver or gold buckle.</p>		

BID FORM

W. E. Caffee
 Assistant Purchasing Agent
 Birmingham, AL

Submitted below is my firm bid for Police uniform items for the City of Birmingham for a period of one (1) year and month to month thereafter in accordance with your Invitation to Bid and specifications dated January 11, 2010. Prices quoted are f.o.b. Birmingham, AL, and I am bidding in exact accordance with the specifications except as listed below.

APPROX QTY.	DESCRIPTION	SYTLE/MFG	UNIT PRICE	EXTENDED TOTAL
GROUP 1: DRESS SHIRTS				
897	Men's Police Winter Shirts – As Per Specs.			
108	Women's Police Winter Shirts – As Per Specs.			
1313	Men's Police Summer Shirts – As Per Specs.			
72	Women's Police Summer Shirts – As Per Specs.			
TOTAL FOR GROUP 1 SHIRTS				\$
GROUP 2: TROUSERS				
1778 pr.	Men's Police Trousers – As Per Specs.			
287 pr.	Women's Police Trousers – As Per Specs.			
TOTAL FOR GROUP 2 TROUSERS				\$
GROUP 3: RAINWEAR				
180	Rainwear Jackets – As Per Specs			
84	Rainwear Pants – As Per Specs.			
TOTAL FOR GROUP 3 RAINWEAR				\$
GROUP 4: JAIL DRESS UNIFORMS				
20	Long sleeve white shirt S – XL			
8	Long sleeve white shirt 2X – 4X			
2	Long sleeve white shirt 5X and larger			
90	Long sleeve grey shirt S – XL			
20	Long sleeve grey shirt 2X – 4XL			
10	Long sleeve grey shirt 5X and larger			
TOTAL FOR LONG SLEEVE SHIRTS				\$
	Alternate Long Sleeve Shirt with Zipper Front			
20	Long sleeve white shirt S – XL			
28	Long sleeve white shirt 2X – 4X			
02	Long sleeve white shirt 5X and larger			
90	Long sleeve grey shirt S – XL			
20	Long sleeve grey shirt 2X – 4XL			
10	Long sleeve grey shirt 5X and larger			
TOTAL FOR ALTERNATE LONG SLEEVE SHIRTS				\$
45	Short Sleeve White Shirt S – XL			
15	Short Sleeve White Shirt 2X – 4X			
10	Short Sleeve White Shirt 5X and larger			
200	Short Sleeve Grey Shirt S – XL			
60	Short Sleeve Grey Shirt 2X – 4X			
20	Short Sleeve Grey Shirt 5X and larger			
TOTAL FOR SHORT SLEEVE SHIRTS				\$

APPROX QTY.	DESCRIPTION	SYTLE/MFG	UNIT PRICE	EXTENDED TOTAL
	Alternate: Short Sleeve with Zipper Front			
45	Short Sleeve White Shirt S – XL			
15	Short Sleeve White Shirt 2X – 4X			
10	Short Sleeve White Shirt 5X and larger			
200	Short Sleeve Grey Shirt S – XL			
60	Short Sleeve Grey Shirt 2X – 4X			
20	Short Sleeve Grey Shirt 5X and larger			
TOTAL FOR ALTERNATE SHORT SLEEVE SHIRT			\$	
400	Trousers per Specifications thru size 42"			
80	Trousers per Specifications 43" – 54"			
20	Trousers per Specifications 55" and larger			
TOTAL FOR TROUSERS			\$	
100	Neckties per Specifications			
TOTAL FOR NECKTIES			\$	
100	Belts per Specifications			
TOTAL FOR BELTS			\$	
TOTAL FOR GROUP 4 JAIL DRESS UNIFORMS			\$	
Shirt percentage mark up for Tall Sizes for Group 4 _____ %				
TOTAL FOR GROUP 1 SHIRTS				\$
TOTAL FOR GROUP 2 TROUSERS				\$
TOTAL FOR GROUP 3 RAINWEAR				\$
TOTAL FOR GROUP 4 JAIL DRESS UNIFORMS				\$
GRAND TOTAL			\$	

I hereby certify that we do not discriminate in employment of our personnel against any persons on account of race, creed, color, sex, or national origins, and acknowledge and agree that the City encourages minority – and women – owned business participation to the maximum extent possible. This policy includes Historically Underutilized Business Enterprises such as architectural firms, engineering firms, investment banking firms, other professional service providers, and construction contractors as part of the City’s business, economic and community revitalization programs.

EXCEPTIONS TO SPECIFICATIONS:

Date of Bid

Company

Street Address

City State Zip

Post Office Box

Tax ID Number

City State Zip

Name (Print or Type)

Terms of Payment

Signature

Delivery Date

Title

Telephone Number

E-Mail Address

Fax Number